

# The Light Source

## Mega-Coupler Pipe Adapter



The Pipe to Coupler Adapter can be used to rig pipe-mounted plasma screens, projectors and speakers from overhead pipe or truss. The Pipe to Coupler Adapter attaches a standard threaded NPT 1-1/2" pipe (1.9" OD) to a Mega-Coupler. There are two interlocking tabs to keep the adapter from rotating. The Adapter is fastened to the Mega-Coupler with the 1/2"-13 tpi by 1-1/4" long bolt and Nylock nut that comes with the Mega-Coupler (not included). There is a 1/4-20 set screw to lock the pipe rotation, and an inspection hole to verify that the pipe is fully inserted.

The Mega-Coupler Pipe Adapter can also be used on a Mega-Claw.

|                           |                                                                                                                                |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>Working Load Limit</b> | 1100 Pounds                                                                                                                    |
| <b>Hardware</b>           | 1/4" × .375 Socket Set Screw                                                                                                   |
| <b>Weight</b>             | 0.8 oz.                                                                                                                        |
| <b>Case Quantities</b>    | each                                                                                                                           |
| <b>Order Codes</b>        | <b>MPI.5B.5M</b> Mega-Coupler Pipe Adapter for 1.5" Pipe, Silver<br><b>MPI.5B.5B</b> Mega-Coupler Pipe Adapter, Black Anodized |